



Cara Insert Matt Black shown

# Cara Eco Insert

The Cara Eco Insert Stove is the ideal home heating solution for those who want the warmth and efficiency of a cast iron stove with all the visual benefits of an open fire. The Cara Eco Insert aims to retain the appearance of an open fire while bringing all the benefits of a stove and is 3 times more efficient than an open fire. It is the perfect solution for where space is at a premium.

## FEATURES

- › Model: Insert Room Heating
- › Fits into a standard fireplace
- › Easily connected to a standard 125mm diameter chimney
- › Large viewing glass
- › Secondary air provides cleaner combustion
- › Window wash air to maintain a clean glass
- › Raised grate for optimum fuel burn
- › Large Ashpan
- › High quality, cast iron build
- › Modern, yet classic design

## DIMENSIONS



## BENEFITS

- › Tested & approved to European standard - EN 13229
- › 5 year warranty
- › Fits into most standard fireplaces
- › Ecodesign 2022 approved

## OPTIONAL EXTRAS

- › External air supply kit - Directs air from the outside into the stove to aid efficient combustion.
- › Cast iron filler piece available in matt black to fit most curved fireplaces


## ROOM HEAT ONLY

Maximum heat output to room **6.5kW**

## PERFECT FOR


- › Heating small to medium sized rooms
- › Replacing an inefficient open fire but retaining all the visual benefits
- › Burning all approved solid fuels

## COLOUR OPTIONS



Enamel  
Black

Matt  
Black



All images shown are for illustration purposes only. Actual product may vary due to product enhancement. Waterford Stanley reserve the right to change product images and specification without notice. The minimum clearance to combustibles required is 550mm to the top, 350mm to the sides, 550mm directly to the front and 350mm to any combustible flooring. If the mantelpiece protrudes further than 100mm from the fireplace, then it will be necessary to have further clearance to the top of the stove. The distance the mantle protrudes past the 100mm should be added to the clearance. For example, if the mantle protrudes 200mm, the clearance to the mantle should be 650mm.