

Waterford Stanley


DECLARATION OF PERFORMANCE

		Efficiency	No _x @ 13% O ₂	Co @ 13% O ₂	OGC @ 13% O ₂	Particulates	Notified body	Test Report
	Model	%	mg/m ³	%	mg/m ³	mg/m ³		
1	Solis I 100 Double	79	125	0.1	16	13	0370	17/14530-1048 S
2	Solis I 80 Double	79	85	0.1	63	31	0370	17/14530-1048 S
3	Solis I 80 Single	78.45	93	0.093	67	14.7	2456	K14992015T1
4	Solis F 500 Edge	81.1	81	0.09	58	28	0558	61162-1
5	Solis F650 style	84.8	92	0.11	109	25	0558	61162-3
6	Solis F 900 Ridge	77.6	91	0.12	117	22	0558	61162-2
7	Solis I 500	81	124	0.1	65	24	1625	RRF-40 17 4688
8	Solis I 900	80	123	0.09	97	12	1625	RRF-40 17 4867
9	Solis F800 Grande	81	123	0.06	47	14	1625	RRF-40 18 5073
10	Solis F1100 Panoramic	80	104	0.09	48	23	1625	RRF-40 18 5071
11	Cara non boiler	78.1	89	0.08	44	24	0558	60861-2
12	Cara glass	78.1	89	0.08	44	24	0558	60861-2
13	Ardmore Eco	81	73	0.12	97	25	0558	61126

The above products have been tested and found to conform with the essential Ecodesign Requirements for Decorative heaters burning wood logs. Product tests carried out as per EN16510 -1.

This declaration of performance is issued under the sole responsibility of the manufacturer
Signed for and on behalf of the manufacturer by:

Noel Hannan – New Product and Technology Introduction Manager



09th Aug 2019

Directors:
Martin Lyndsay, Agustin Zufia